

Type	Technical Data									Weight			Dimension		Tower		
	Power output (kW)	Rotor diameter (m)	Cut-in wind speed (m/s)	Rated wind speed (m/s)	Cut-out wind speed (m/s)	Extreme wind speed (m/s)	Survival temperature (°C)	Operating temperature (°C)	Wind class	Nacelle (T)	Rotor (incl. blades) (T)	Single blade (T)	Nacelle (m)	Hub (m)	Type	Height (m)	
MySE3.0-112	3,000	112	3.0	11.0	25.0	70.0	-40~50	-30~40	IEC S	83.0	78.0	14.0	L 6.80 W 3.30 H 3.89	L 4.20 W 3.87 H 3.36	Tubular steel	85/ 90/ 100/ 120/ 130/ 140	
MySE3.0-121		121		10.0													
MySE3.0-135		135		9.3	20.0												52.5/70
MySE3.2-145		145		2.5													
MySE3.6-135		135		3.0	9.8												20(25)



MINGYANG DEFWENG ENERGY SYSTEMS CO.LTD
 Address: 22 Torch Road, Ming Yang Industrial Park,
 National Torch Hi-Tech Industrial Development Zone,
 Zhongshan, Guangdong, P.R.China.
 Tel: +86 760 2813 8666
 Fax: +86 760 2813 8667
 Postcode: 528437
<http://www.mywind.com.cn>

MINGYANG SMART ENERGY



 MINGYANG SMART ENERGY

MySE 3.X MW

HYBRID DRIVE WTG

